



Notes;

- 1.Plug: JT-SZ3 10A 250V~ Clear injection, no scratch and dirt
- 2.Cable:H05VV-F 3X1.0 mm²Jacket ϕ 6.8 \pm 0.1 Conductor 32 \times 0.2, Core ϕ 2.6 \pm 0.1 ϕ 2.4 \pm 0.1
Cable Mark : ◁VDE▷ H05VV-F 3X1.0mm²
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S, External Voltage AC6000V/1S, current leakage 1mA, insulation resistance no less than 50M Ω , no strike out

11	CH30	H05VV-F 3G1.0mm ²	500 \pm 10mm	Black
10	CH29	H05VV-F 3G1.0mm ²	300 \pm 10mm	Black
9	CH28	H05VV-F 3G1.0mm ²	25000 \pm 50mm	Black
8	CH27	H05VV-F 3G1.0mm ²	20000 \pm 50mm	Black
7	CH26	H05VV-F 3G1.0mm ²	15000 \pm 50mm	Black
6	CH25	H05VV-F 3G1.0mm ²	10000 \pm 50mm	Black
5	CH24	H05VV-F 3G1.0mm ²	7500 \pm 50mm	Black
4	CH23	H05VV-F 3G1.0mm ²	5000 \pm 50mm	Black
3	CH22	H05VV-F 3G1.0mm ²	3000 \pm 30mm	Black
2	CH21	H05VV-F 3G1.0mm ²	1800 \pm 15mm	Black
1	CH20	H05VV-F 3G1.0mm ²	1000 \pm 10mm	Black
Item	Customer Model	Model/No.	Length(mm)	Color

P.N	Item	JT-SZ3/JT-ST3	Drw. N	JT-YP-03135
Dre By	Ni Shaojian		Date	
Check By		.x \pm 0.15 .x' \pm 0.15 .xx \pm 0.25 .xx' \pm 0.25 .xxx \pm 0.38 .xxx' \pm 0.38	1 : 1	mm