



Notes;

- 1.Plug: JT-SZ3 10A 250V~ Clear injection, no scratch and dirt
- 2.Cable:H05VV-F 3X1.0 mm<sup>2</sup> Jacket  $\phi$ 6.8 $\pm$ 0.1 Conductor 32 $\times$ 0.2, Core  $\phi$ 2.6 $\pm$ 0.1  $\phi$ 2.4 $\pm$ 0.1  
Cable Mark :  $\triangleleft$ VDE $\triangleright$  H05VV-F 3X1.0mm<sup>2</sup>
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S, External Voltage AC6000V/1S, current leakage 1mA, insulation resistance no less than 50M $\Omega$ , no strike out

6	CH83	H05VV-F 3G1.0mm <sup>2</sup>	5000 $\pm$ 50mm	White
5	CH82	H05VV-F 3G1.0mm <sup>2</sup>	3000 $\pm$ 30mm	White
4	CH81	H05VV-F 3G1.0mm <sup>2</sup>	1800 $\pm$ 20mm	White
3				
2				
1				
Item	Customer Model	Model/No.	Length (mm)	Color

P.N	Item	JT003/JT-ST3	Drw. N	JT-YP-03136
Dre By	Ni Shaojian		Date	
Check By		.x $\pm$ 0.15 .x' $\pm$ 0.15 .xx $\pm$ 0.25 .xx' $\pm$ 0.25 .xxx $\pm$ 0.38 .xxx' $\pm$ 0.38	1 : 1	mm

