



Notes;

- 1.Plug: JT-SZ3 10A 250V~ Clear injection, no scratch and dirt
- 2.Cable:H05VV-F 3X1.0 mm²Jacket $\phi 6.8 \pm 0.1$ Conductor 32×0.2 , Core $\phi 2.6 \pm 0.1$ $\phi 2.4 \pm 0.1$
Cable Mark : \triangleleft VDE \triangleright H05VV-F 3X1.0mm²
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S, External Voltage AC6000V/1S, current leakage 1mA, insulation resistance no less than 50M Ω , no strike out

9	FA86	H05VV-F 3G1.0mm ²	15000±50mm	Black
8	FA85	H05VV-F 3G1.0mm ²	10000±50mm	Black
7	FA84	H05VV-F 3G1.0mm ²	7500±50mm	Black
6	FA83	H05VV-F 3G1.0mm ²	5000±50mm	Black
5	FA82	H05VV-F 3G1.0mm ²	3000±30mm	Black
4	FA81	H05VV-F 3G1.0mm ²	1800±20mm	Black
3	FA80	H05VV-F 3G1.0mm ²	1500±15mm	Black
2	FA79	H05VV-F 3G1.0mm ²	1200±10mm	Black
1	FA78	H05VV-F 3G1.0mm ²	300±10mm	Black
Item	Customer Model	Model/No.	Length (mm)	Color

P.N	Item	JT003/JT-ST3	Drw. N	JT-YP-03136
Dre By	Ni Shaojian		Date	
Check By		.x±0.15 .x'±0.15 .xx±0.25 .xx'±0.25 .xxx±0.38 .xxx'±0.38	1 : 1	mm

